

## M-iClean HL

Execution for: Great Britain

### Glass washer

Working direction: right - left

Working height: 850 mm

3-phase current: 3N PE 400V 50Hz

Fresh water line: Soft cold water 0-3°dH

GiO-module (separate)

Heat retention

Waste water heat recovery

Automatic hood opening

Power Wash



Sample illustration

### Technical data

<b>Rack capacity/h (theoretical)</b>	40 / 30 / 30 racks/h
<b>Programme cycle time</b>	90 / 120 / 120 s
<b>Rack dimension</b>	500 x 500 mm (650 x 500 mm)
<b>Entry height</b>	560 mm
<b>Dimensions (W x Hmin x D)</b>	735 ( 825) x 2210 x 750 (800) mm (with handles)
<b>Electrical feeding cable</b>	3-phase current: 3N PE 400V 50Hz Total connected load: 9.9 kW max. rated current: 16.3 A
<b>Local fuse protection</b>	20 A
<b>Protection class of the machine</b>	IP X5
<b>Packages</b>	PureEnergy package
<b>Equipment</b>	Control system MIKE-CPU4 Bluetooth interface for wireless communication Leakage detector Boiler safety device Automatic self-cleaning when tank is drained Drain pump Back wall cladding Power Wash Automatic hood opening Heat retention Waste water heat recovery Integrated reverse osmosis (separate, with connection and discharge set) Bracket for integrated reverse osmosis unit, right Chlorine-resistant membrane

# Technical Information



The clean solution

<b>Fresh water line</b>	For reverse osmosis: connecting set with stop valve, Pressure regulator, filter 10 µm with activated carbon Internal: air gap 'AA' in accordance with EN 1717 with booster pump
<b>Fresh water supply</b>	Minimum flow pressure 100 kPa / 1.0 bar in front of solenoid valve Maximum pressure 500 kPa / 5.0 bar in front of pressure reducer Max. supply water temperature 35 °C
<b>Flow rate</b>	total 7.3 l/min (at 15 °C inlet temperature and a flow pressure of 200 kPa / 2 bar) Permeate 2.8 l/min Concentrate 4.5 l/min
<b>Fresh water thresholds</b>	Temperature cold water min. 1 °C to max. 35 °C Conductivity < 1000 µS/cm Total hardness max. 28 dH / 5mmol/l CaCO <sub>3</sub> Free of particles > 10 µm Iron < 0.10 mg/l Manganese < 0.04 mg/l Chlorine > 0.10 mg/l (free chlorine) Potassium permanganate < 10 mg/l Silicic acid < 10 mg/l
<b>Final rinse water quantity</b>	3.0 liters/cycle, variable
<b>Boiler</b>	Contents: 10.5 l Heater: 8.00 kW Temperature: 65 °C Tank / boiler locked
<b>Wash tank</b>	Filling: 22.0 l Heater: 4.00 kW Temperature: 60 °C
<b>Wash pump, with frequency converter</b>	Performance: 1.50 kW
<b>Dosing of rinse aid</b>	Hose pump (24 V) with time control and suction lance
<b>Detergent dosage</b>	Hose pump (24 V) with time control and suction lance
<b>Material</b>	Cladding: 1.4301 Wash tank: 1.4301 Boiler: 1.4571
<b>Heat emission</b>	for 25 programme cycles/h total: 2.2 kW perceptible: 1.8 kW latent: 0.4 kW
<b>Ventilation flow rate</b>	570 m <sup>3</sup> /h
<b>Steam emission</b>	0.7 kg/h