

WAREWASHER UX-50B (MULTI POWER)

Commercial glass- and dishwasher. Rack size 500 x 500 mm and door clearance 380 mm. Multi-power version. Power configurable to 13 / 16 / 20 / 25 amp option.



fragile items.

✓ Soft start: progressive start-up of the washing pump to protect fragile items.
✓ Colour LCD Display: intuitive communication of the machine state.

√ Ultra Xperience: high performance, without complications.

"Easy grip" door: new design with integrated door handle

√ The integration of the components provides greater resistance and

Designed to have no corners or areas that are difficult to access:

Its ergonomic handle provides a perfect grip, even with wet hands.
 Double-walled door with safety microswitch and high quality seal
 38 cm loading capacity: high versatility for washing a wide range of items: dishes, Euronorm trays, GN 1/1 tubs and pizza plates diam 39

prevents deposits of dirt and facilitates cleaning.

- Colour LCD Display: intuitive communication of the machine status by means of messages, colour codes and icons.
- Dedicated cycles: selection of the ideal washing programme using icons.
- Adaptable: allows the main parameters of the machine to be adjusted to the needs of each user.
- ✓ TEMPERATURE DISPLAY

Premium warewashing

- Wash Plus+ function: increases the intensity of the wash cycle for greater cleaning performance
- ✓ Control panel with IP65 humidity protection.

SALES DESCRIPTION

Sani-Control: guaranteed disinfection.

Embedded bodywork and easy-grip door: hygienic and ergonomic

Exclusive Hydroblade™ washing arms: maximum effectiveness.

3-stage filtering system.

Double-walled body (partial).

Multi-power model.

Sani-Control guarantee

- GUARANTEED DISINFECTION in compliance with standard DIN 10534.
- √ THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.

New recessed bodywork

- Ergonomic design with rounded corners to prevent the accumulation of dirt and facilitate cleaning.
- Compact tank volume (50% water saving compared to the previous range).
- √ Embedded basket guides

Hydroblade™ washing arms

- \checkmark Redesigned nozzles for greater washing performance.
- The "monoblock" design delivers durability and resistance to impacts.
- 30% savings in water consumption during rinsing compared to the previous range.

3-stage filter system: surface, tank and extraction

- Keeps the washing water in optimal conditions to maintain constant washing performance.
- The surface filters feature an "easy-on" design and can be quickly removed without having to disconnect the washing arms.



You will never WASH ALONE

- Tech-Services: our team of technicians will help you so that your machine is always ready for use.
- ✓ Design Services: tell us what your needs are and we will advise you.
- √ 60 years of experience and know-how at your disposal.

NCLUDES

- ✓ Peristaltic Detergent Pump.
- ✓ Rinse aid pump.
- √ 1 glasses basket.
- √ 1 mixed basket (plates).
- √ 1 small basket for cutlery.

OPTIONAL

- Manual resin regeneration water softener.
- Double-level accessory for washing two baskets at the
- same time.
- Drainage pump with level sensor. Proactive tank water renewal.

Accessories

- Manual water softeners
- Automatic water softeners
- ☐ 500 x 500 mm baskets
- ☐ Inserts & supplements
- High feet kit
- ☐ Reverse osmosis devices OS-140
- □ Double rack kits for AX/UX

SPECIFICATIONS

Basket dimensions: $500 \, \text{mm} \, \text{x} \, 500 \, \text{mm}$

Useful height: 380 mm

Oycle duration: 90 / 110 / 120 / 180 / 240" Production baskets / hour: 40 / 33 / 30 / 20 / 15

Wash temperature: - 65°C Rinse temperature: 65°C - 87°C

Boiler capacity: 8 I Wash tank capacity: 14 I

Consumption and savings

Water consumption/cycle: 2.5 I Automatic saving mode in: 25'



WAREWASHER UX-50B (MULTI POWER)

Commercial glass- and dishwasher. Rack size 500 x 500 mm and door clearance 380 mm. Multi-power version. Power configurable to 13 / 16 / 20 / 25 amp option.

Automatic switch-off: 120'

Loading

Pump: 750 W / 1 Hp Tank: 1800 W

Total loading: 2550 / 4550 / 5550 W (single phase) / (multipower)

External dimensions (W x D x H)

- √ Width:580 mm
- ✓ Depth: 635 mm
- √ Height: 835 mm

Net weight: 57 kg

Noise level (1m.): <69 dB(A)

Crated dimensions

640 x 695 x 960 mm

Available Models			
1303222	UX-50 400/50/3N DD		
1303223	UX-50 220/60/1 DD		
1303226	UX-50B 230/50/1 DD		
1303227	UX-50B 400/50/3N DD		
1303230	UX-50D 400/50/3N DD		
1303233	UX-50BD 400/50/3N DD		
1303235	UX-50BD 230/50/1 DD 580		
1303212	UX-50B 220/60/1 DD 22 53/64		
1303237	UX-50BD 230/50(1 DD	_	
* Ask for s	special versions availability 998 28		
	540 21 17/64 500		



539 21 7/32

19 11/16 A

- B: Entrada de agua 3/4" GAS.
- C: Cable conexión.

250

9 27/32 330

12 63/64



105

4 1/8

Project	Date
Item	Qty

402

15 13/16

370

340

Approved

19 27/64 640

25 3/16

www.sammic.co.uk

Food Service Equipment Manufacturer Unit 2, Trevanth Road Troon Industrial Park LE4 9LS - Leicester

uksales@sammic.com Tel.: +44 0116 246 1900

sammic